



TEST DATA SHEET “ RUBBER PROCESS OIL 145”

DESCRIPTION	RESULT	TEST METHODE
KINEMATIC VISCOSITY 100° C	40-50	ASTMD 445
FLASH POINT (°C) Min	240	ASTM D 92
ANILINE POINT (°C)	30-40	ASTM D 611
POUR POINT (°C) Max	+27	ASTM D 97
DENSITY @ 15.6°C (g/cm3) typical	1.02	ASTM D 4052
VGC (typical)	0.97	ASTM D 2501

Application

Passenger car tyre remained the leading market segment in 2013, holding significant majority share in volume as well as value sales. Urban cities in the uae such as dubai, abu dhabi and sharjah are among the leading demand generators for tyres. Industry events such as automechanika' and green auto show' also have a profound impact on the uae's ever-growing automotive trade, which in turn are influencing tyre sales in the country. Global automotive tyre manufacturers such as bridgestone, michelin, continental, goodyear, and pirelli are the key tyre players in the country.

Packing

Rubber Process Oil packed in new or used 200 kg drums, iso tank , flexi tanks and bulk shipments. Each 20 foot container takes 80 drums.

No42, 4th Floor, Sepehr Building, Bahonar Street, Isfahan, Iran

- Tel: +98-3133458785
- Fax: +98-3133458781
- Website: www.globallybitumen.com www.pub-ltd.com
- E_mails : info@globallybitumen.com info@pub-ltd.com